

Serial No. 10/074,893  
Amendment dated November 16, 2004  
Reply to Office Action of September 16, 2004

**Amendment to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application.

**Listing of Claims:**

1-7. (canceled)

8. (Previously Presented) A metal air cell comprising:
- a cathode having a pair of oxidant sides and anode sides;
  - a cartridge having a pair of inside surfaces for housing an anode, the anode provided in two parts, each part having a side complementary each anode side of the cathode, the cartridge further comprising a reservoir at an end opposite an insertion end, the reservoir having electrolyte or liquid therein; and
  - a separator between the anode and cathode to electrically isolate the anode and the cathode,
  - wherein an electrolyte is disposed between the cathode and the anode, the electrolyte provided within the anode, separately at the interface between the cathode and the anode, or both within the anode and separately at the interface between the cathode and the anode.

9. (Previously Presented) The metal air cell as in claim 8, wherein the cathode is within a structure, the structure having a portion complementing the reservoir, such

Serial No. 10/074,893  
Amendment dated November 16, 2004  
Reply to Office Action of September 16, 2004

that when the cathode and the anode are brought into ionic communication the electrolyte or liquid within the reservoir is spread to the interface between the anode and the cathode.

10. (Previously Presented) The metal air cell as in claim 8, wherein the cathode is supported on a frame.

11. (Previously Presented) The metal air cell as in claim 10, wherein the frame is configured to provide a conduit in fluid communication with the pair of oxidant sides of the cathode.

12. (Previously Presented) The metal air cell as in claim 8, wherein oxidant is provided to the cathode separate from cooling air.

13. (Previously Presented) The metal air cell as in claim 8, wherein separator is adhered to the cathode.

14. (Previously Presented) The metal air cell as in claim 8, wherein separator is adhered to the anode.

Serial No. 10/074,893  
Amendment dated November 16, 2004  
Reply to Office Action of September 16, 2004

15. (Previously Presented) A metal air cell comprising:
- a cathode having an oxidant surface and an anode surface, the cathode being supported on a frame configured to provide a conduit in fluid communication with the oxidant surface;
- an anode complementary the cathode's anode surface; and
- a separator between the anode and cathode to electrically isolate the anode and the cathode,
- wherein an electrolyte is disposed between the cathode and the anode, the electrolyte provided within the anode, separately at the interface between the cathode and the anode, or both within the anode and separately at the interface between the cathode and the anode.
16. (Previously Presented) The metal air cell as in claim 15, wherein the anode is supported by two inside surfaces of a cartridge.
17. (Previously Presented) The metal air cell as in claim 16, the cartridge further comprising a reservoir at an end opposite an insertion end, the reservoir having electrolyte or liquid therein.

Serial No. 10/074,893  
Amendment dated November 16, 2004  
Reply to Office Action of September 16, 2004

18. (Previously Presented) The metal air cell as in claim 17, wherein the cathode is within a structure, the structure having a portion complementing the reservoir, such that when the cathode and the anode are brought into ionic communication the electrolyte or liquid within the reservoir is spread to the interface between the anode and the cathode.

19. (Previously Presented) The metal air cell as in claim 15, wherein oxidant is provided to the cathode separate from cooling air.

20. (Previously Presented) The metal air cell as in claim 15, wherein separator is adhered to the cathode.

21. (Previously Presented) The metal air cell as in claim 15, wherein separator is adhered to the anode.

22. (Canceled) A metal air cell comprising:  
a cathode having an oxidant side and an anode side,  
the cathode being supported on a frame,  
the frame configured to provide a conduit in fluid communication with the oxidant side.